


FIG. 1






FIG. 2

28

Transport QoS profile[3]

|                |                    |                |
|----------------|--------------------|----------------|
| client has?[1] | grant by server[1] | sub-profile[1] |
|----------------|--------------------|----------------|

45a

Client info -> OS type

|        |               |
|--------|---------------|
| 0x0001 | WINDOWS NT    |
| 0x0002 | WINDOWS 2000  |
| 0x0003 | WINDOWS 98    |
| 0x0004 | WINDOWS 95    |
| 0x0005 | WIN32 generic |
| 0x0006 | OTHER         |

42a

Client info->  
server/wkstation[3]

|             |               |                       |
|-------------|---------------|-----------------------|
| validity[1] | server [0x01] | workstation<br>[0x00] |
|-------------|---------------|-----------------------|

42b

Client info ->  
processor\_architecture[8]

|        |       |
|--------|-------|
| 0x0001 | Intel |
| 0x0002 | MIPS  |
| 0x0003 | ALPHA |
| 0x0004 | PPC   |
| 0x0005 | OTHER |

42c

Client info ->  
ethernet[8]

|      |          |
|------|----------|
| 0x00 | 10BaseT  |
| 0x01 | 100BaseT |
| 0x02 | Gigabit  |

42d

FIG. 3




FIG. 4




FIG. 5




FIG. 6a

